

Ponds & Basins



Ponds and basins are implemented to collect and store water from river runoff. Hence, they are built adjacent to these water bodies and often in floodplains. Two types are recognised: 1) retention – which refers to a pond/basin that is permanently covered by water; and 2) detention – referring to a pond/basin that is temporarily covered by water, especially during times of high discharge.

Ponds and basins build habitats for water and land animals and, therefore, can increase biodiversity. Variation in water depths can be beneficial for diversity. The water storage and slow infiltration into soil has a purifying effect on the water. Depending on the design of the pond/basin, they can provide spaces for recreational activities.

In general, ponds and basins are more effective for flood peak reduction if there are multiple of them or if they are combined with other Nature-based Solutions.

Overview

Type	Blue
Approach	Implementation
Hazard	They can be implemented to reduce the risk on Riverine Flooding .
Multi-hazard	Overall, ponds and basins can be implemented to reduce surface runoff and therefore Fluvial/Urban Flooding . With their ability to store water and recharge groundwater, they can mitigate Hydrological Droughts .

SDGs



Direct Benefits

Runoff Storage

Ponds and Basins are designed to store water of high precipitation events. The capacity depends naturally on the size. A minimum was suggested of 500 m³ but can also reach to 1 km³. Furthermore, the storage capacity is defined by the characteristic of the NBS – whether it is a detention or retention pond/basin.

Groundwater Recharge

The storage and infiltration of water is valuable for dry periods as it recharges groundwater. The recharge may be determined by the soil texture and type (retention/detention) of the intervention.

**Co-benefits/
Disbenefits**
Water Quality

Infiltration of surface runoff can purify water before reaching the groundwater.

Biodiversity

Retention ponds and basins can increase biodiversity by providing habitats for different species. Designing the pond/basin with different water depths will invite more species to reside. While detention ponds can be maintained by grazing and therefore offers a temporary habitat for grazing animals.

Ecosystem Disservices

Retention ponds and basins also provide habitats for mosquitoes which are often perceived as disbenefits.

Furthermore, retention ponds with standing water are at risk of algae bloom which can be prevented with measures such as a fountain in order to keep the ecosystem alive.

Costs

The costs vary greatly between different sources. Around 44 000 €/ha was reported by NWRM (2015). Stella Consulting (2012) provides costs per EU Member State. Construction costs were also reported in cubic meter with 9 - 91€/m³ (Middlesex University, 2003). Due to older sources, prices may be higher than reported here.

Maintenance: up to 60€/m³

Additional costs: land acquisition

**NBS Related
Policies**

- Water Framework Directive
- Floods Directive
- Habitats and Birds Directive
- EU Green Deal
- EU Biodiversity Strategy to 2020

Funding Options

- European Green Deal

Design Implementation

Scale

Microscale/single/scattered/local (1 m - 1 km)

Size

Ponds and basins are suggested to be between 1.2 - 5 m deep, with a minimum area of 150 m² and a capacity of up to 1 km³ water. However, the size of the pond/basin should be aligned to the size of the river/stream and the drainage area.

Slope

Max. 60 %

Elevation

They are not suitable for coasts and mountainous areas; thus, an elevation between 20 and 1000 m is suggested.

Land Cover

Urban, Cropland, Grassland, Woodland and forest, Heathland and shrub, Sparsely vegetated land

Soil Texture

All types can be suitable

Soil depth	A minimum of 2-3 m
Bulk density	<i>No limitations found</i>
Implementation	<p>They are commonly implemented in already vegetated areas. Furthermore, their banks and surroundings are commonly vegetated which causes a small amount of maintenance costs.</p> <p>They are suitable for all climate zones.</p>
Cautions	<p>Ponds and basins should not be implemented in unstable areas that are prone to landslides.</p> <p>Small-scale ponds with standing water can be at risk of algae blooming. This may be anticipated with e.g., a fountain.</p>

NBS Suitability Mapping

(Below are the layers and specifications listed that were used for analysing the suitability of this Nature-based Solution for your area)

Land Cover	Urban green areas, Cropland, Grassland, Woodland and forest, Heathland and shrub, Sparsely vegetated land [LUISA Base Map 2018, Batista and Pigaiani, 2021]
Infrastructure	Buildings (areas without buildings) [ESM, Corbane and Sabo, 2019]
Soil depth	Min. 2 m [Absolute depth to bedrock, ISRIC, 2017]
Surface water	Rivers (1), Lakes (0)
Elevation	20-1000 m
Slope	Max. 60 % [Slope Angle, Wilde et al., 2018]
Landslide Susceptibility	Susceptible areas (0), all other (1) [European Landslide Susceptibility Map version 2 (ELSUS v2), Wilde et al., 2018]

References

Batista, F., Pigaiani, C. (2021) 'LUISA Base Map 2018. European Commission, Joint Research Centre (JRC)' [Dataset] PID: <http://data.europa.eu/89h/51858b51-8f27-4006-bf82-53eba35a142c>.

Brueck, P., Mubareka, S., Ad de Roo, R. R., Bianchi, A., Baranzelli, C., Lavallo, C., Vandecasteele, I. (2012) 'Evaluation of the effectiveness of Natural Water Retention Measures'. Available at: https://ec.europa.eu/environment/water/blueprint/pdf/EUR25551EN_JRC_Blueprint_NWRM.pdf.

Corbane, Christina; Florczyk, Aneta; Pesaresi, Martino; Politis, Panagiotis; Syrris, Vasileios (2018): GHS built-up grid, derived from Landsat, multitemporal (1975-1990-2000-2014), R2018A. European Commission, Joint Research Centre (JRC) [Dataset] doi: 10.2905/jrc-ghsl-10007 PID: <http://data.europa.eu/89h/jrc-ghsl-10007>.

Corbane, Christina; Sabo, Filip (2019) 'European Settlement Map from Copernicus Very High Resolution data for reference year 2015', Public Release 2019. European Commission, Joint Research Centre (JRC) [Dataset] doi: 10.2905/8BD2B792-CC33-4C11-AFD1-B8DD60B44F3B PID: <http://data.europa.eu/89h/8bd2b792-cc33-4c11-afd1-b8dd60b44f3b>.

DayWater (2003) 'Report 5.1 Review of the Use of stormwater BMPs in Europe'. Available at: <https://www.leesu.fr/daywater/REPORT/D5-1.pdf>.

ISRIC (2017) 'SoilGrids250m 2017-03 – Absolute depth to bedrock' [Dataset]. Available at: <https://data.isric.org/geonetwork/srv/eng/catalog.search#/metadata/f36117ea-9be5-4afd-bb7d-7a3e77bf392a>.

NWRM (2015) 'Natural Water Retention Measures'. Available at: <http://nwrn.eu>.

Stella Consulting (2012) 'Cost, benefits and climate proofing of natural water retention measures'. Available at: https://coordinamentoassociazionidfteverefarfa.files.wordpress.com/2015/11/nat-water-retention-measures-stella-2012_finalreport.pdf.

Wilde, M., Günther, A., Reichenbach, P., Malet, J.-P., Hervás, J. (2018) 'Pan-European landslide susceptibility mapping: ELSUS Version 2' [Dataset]. Available at: <https://esdac.irc.ec.europa.eu/content/european-landslide-susceptibility-map-elsus-v2>.